

ROLLER BALL LOCK TYPE CABLE TIES

UNCOATED



Technical Specifications

Material	304 and 316L grade non-magnetic stainless steel
Temperature Range	-60 C to +300°C
Surface Finish	Metallic
Flamability Rating	UL 94 Fireproof & UV Resistant



Part Code as per Stainless Steel Grade		Width		Length		Thickness		Max. Loop Diameter		Max. Loop Tensile Strength		Package Quantity
SS304	SS316L	Inch	mm	Inch	mm	Inch	mm	Inch	mm	N	lbs	Pcs
CBU14-100	CBU16-100	0.18	4.6	4	100	0.01	0.25	0.94	24	667	150	100
CBU14-127	CBU16-127	0.18	4.6	5	127	0.01	0.25	1.02	26			
CBU14-150	CBU16-150	0.18	4.6	6	150	0.01	0.25	1.57	40			
CBU14-200	CBU16-200	0.18	4.6	8	200	0.01	0.25	2.20	56			
CBU14-260	CBU16-260	0.18	4.6	10	260	0.01	0.25	2.95	75			
CBU14-300	CBU16-300	0.18	4.6	12	300	0.01	0.25	3.46	88			
CBU14-360	CBU16-360	0.18	4.6	14	360	0.01	0.25	4.21	107			
CBU14-400	CBU16-400	0.18	4.6	16	400	0.01	0.25	4.53	115			
CBU14-450	CBU16-450	0.18	4.6	18	450	0.01	0.25	5.31	135			
CBU14-520	CBU16-520	0.18	4.6	20	520	0.01	0.25	6.22	158			
CBU14-550	CBU16-550	0.18	4.6	22	550	0.01	0.25	6.38	162			
CBU14-620	CBU16-620	0.18	4.6	24	620	0.01	0.25	7.48	190			
CBU14-680	CBU16-680	0.18	4.6	27	680	0.01	0.25	7.87	200			
CBU14-840	CBU16-840	0.18	4.6	33	840	0.01	0.25	10.24	260			
CBU14-1000	CBU16-1000	0.18	4.6	39	1000	0.01	0.25	12.24	311			

Part Code as per Stainless Steel Grade		Width		Length		Thickness		Max. Loop Diameter		Max. Loop Tensile Strength		Package Quantity
SS304	SS316L	Inch	mm	Inch	mm	Inch	mm	Inch	mm	N	lbs	Pcs
CBU24-100	CBU26-100	0.31	7.9	4	100	0.01	0.25	0.94	24	1335	300	100
CBU24-127	CBU26-127	0.31	7.9	5	127	0.01	0.25	1.02	26			
CBU24-150	CBU26-150	0.31	7.9	6	150	0.01	0.25	1.57	40			
CBU24-200	CBU26-200	0.31	7.9	8	200	0.01	0.25	2.20	56			
CBU24-260	CBU26-260	0.31	7.9	10	260	0.01	0.25	2.95	75			
CBU24-300	CBU26-300	0.31	7.9	12	300	0.01	0.25	3.46	88			
CBU24-360	CBU26-360	0.31	7.9	14	360	0.01	0.25	4.21	107			
CBU24-400	CBU26-400	0.31	7.9	16	400	0.01	0.25	4.53	115			
CBU24-450	CBU26-450	0.31	7.9	18	450	0.01	0.25	5.31	135			
CBU24-520	CBU26-520	0.31	7.9	20	520	0.01	0.25	6.22	158			
CBU24-550	CBU26-550	0.31	7.9	22	550	0.01	0.25	6.38	162			
CBU24-620	CBU26-620	0.31	7.9	24	620	0.01	0.25	7.48	190			
CBU24-680	CBU26-680	0.31	7.9	27	680	0.01	0.25	7.87	200			
CBU24-840	CBU26-840	0.31	7.9	33	840	0.01	0.25	10.24	260			
CBU24-1000	CBU26-1000	0.31	7.9	39	1000	0.01	0.25	12.24	311			

Part Code as per Stainless Steel Grade		Width		Length		Thickness		Max. Loop Diameter		Max. Loop Tensile Strength		Package Quantity
SS304	SS316L	Inch	mm	Inch	mm	Inch	mm	Inch	mm	N	lbs	Pcs
CBU34-100	CBU36-100	0.5	12	4	100	0.01	0.25	0.94	24	2000	450	100
CBU34-127	CBU36-127	0.5	12	5	127	0.01	0.25	1.02	26			
CBU34-150	CBU36-150	0.5	12	6	150	0.01	0.25	1.57	40			
CBU34-200	CBU36-200	0.5	12	8	200	0.01	0.25	2.20	56			
CBU34-260	CBU36-260	0.5	12	10	260	0.01	0.25	2.95	75			
CBU34-300	CBU36-300	0.5	12	12	300	0.01	0.25	3.46	88			
CBU34-360	CBU36-360	0.5	12	14	360	0.01	0.25	4.21	107			
CBU34-400	CBU36-400	0.5	12	16	400	0.01	0.25	4.53	115			
CBU34-450	CBU36-450	0.5	12	18	450	0.01	0.25	5.31	135			
CBU34-520	CBU36-520	0.5	12	20	520	0.01	0.25	6.22	158			
CBU34-550	CBU36-550	0.5	12	22	550	0.01	0.25	6.38	162			
CBU34-620	CBU36-620	0.5	12	24	620	0.01	0.25	7.48	190			
CBU34-680	CBU36-680	0.5	12	27	680	0.01	0.25	7.87	200			
CBU34-840	CBU36-840	0.5	12	33	840	0.01	0.25	10.24	260			
CBU34-1000	CBU36-1000	0.5	12	39	1000	0.01	0.25	12.24	311			