

LADDER TYPE CABLE TIES

COATED



Technical Specifications

Material	304 and 316L grade non-magnetic stainless steel
Temperature Range	-60° C to +150°C
Surface Finish	Pure Polyester Coating
Flamability Rating	UL 94 Fireproof & UV Resistant



Part Code as per Stainless Steel Grade		Width		Length		Thickness		Max. Loop Diameter		Max. Loop Tensile Strength		Package Quantity
SS304	SS316L	Inch	mm	Inch	mm	Inch	mm	Inch	mm	N	lbs	Pcs
CLC14-100	CLC16-100	0.28	7	4	100	0.012	0.3	0.94	24	400	90	100
CLC14-150	CLC16-150	0.28	7	6	150	0.012	0.3	1.89	48			
CLC14-200	CLC16-200	0.28	7	8	200	0.012	0.3	2.52	64			
CLC14-225	CLC16-225	0.28	7	9	225	0.012	0.3	2.83	72			
CLC14-250	CLC16-250	0.28	7	10	250	0.012	0.3	3.15	80			
CLC14-300	CLC16-300	0.28	7	12	300	0.012	0.3	3.78	96			
CLC14-350	CLC16-350	0.28	7	14	350	0.012	0.3	4.33	110			
CLC14-360	CLC16-360	0.28	7	14	360	0.012	0.3	4.53	115			
CLC14-400	CLC16-400	0.28	7	16	400	0.012	0.3	5.28	134			
CLC14-450	CLC16-450	0.28	7	18	450	0.012	0.3	5.63	143			
CLC14-500	CLC16-500	0.28	7	20	500	0.012	0.3	6.54	166			
CLC14-550	CLC16-550	0.28	7	22	550	0.012	0.3	7.13	181			
CLC14-610	CLC16-610	0.28	7	24	610	0.012	0.3	7.64	194			
CLC14-750	CLC16-750	0.28	7	30	750	0.012	0.3	9.41	239			
CLC14-1000	CLC16-1000	0.28	7	39	1000	0.012	0.3	12.52	318			

Part Code as per Stainless Steel Grade		Width		Length		Thickness		Max. Loop Diameter		Max. Loop Tensile Strength		Package Quantity
SS304	SS316L	Inch	mm	Inch	mm	Inch	mm	Inch	mm	N	lbs	Pcs
CLC24-100	CLC26-100	0.47	12	4	100	0.012	0.3	0.94	24	800	180	100
CLC24-150	CLC26-150	0.47	12	6	150	0.012	0.3	1.89	48			
CLC24-200	CLC26-200	0.47	12	8	200	0.012	0.3	2.52	64			
CLC24-225	CLC26-225	0.47	12	9	225	0.012	0.3	2.83	72			
CLC24-250	CLC26-250	0.47	12	10	250	0.012	0.3	3.15	80			
CLC24-300	CLC26-300	0.47	12	12	300	0.012	0.3	3.78	96			
CLC24-350	CLC26-350	0.47	12	14	350	0.012	0.3	4.33	110			
CLC24-360	CLC26-360	0.47	12	14	360	0.012	0.3	4.53	115			
CLC24-400	CLC26-400	0.47	12	16	400	0.012	0.3	5.28	134			
CLC24-450	CLC26-450	0.47	12	18	450	0.012	0.3	5.63	143			
CLC24-500	CLC26-500	0.47	12	20	500	0.012	0.3	6.54	166			
CLC24-550	CLC26-550	0.47	12	22	550	0.012	0.3	7.13	181			
CLC24-610	CLC26-610	0.47	12	24	610	0.012	0.3	7.64	194			
CLC24-750	CLC26-750	0.47	12	30	750	0.012	0.3	9.41	239			
CLC24-1000	CLC26-1000	0.47	12	39	1000	0.012	0.3	12.52	318			